

Mynute i

High efficiency system boiler

RANGE - i20 - i30

ERP CLASS A

REAR FLUE OPTION

10:1 MODULATION RATIO

BUILT-IN RELAY



ErP
2015 COMPLIANT

Mynute i

High efficiency system boiler

SPECIFICATIONS	Mynute i20	Mynute i30
Product order code	20101253	20101256
Central Heating		
Heat input (kW)	20	30
Maximum heat output @ 80°C/60°C (kW)	19.6	29.2
Modulation Ratio		
Modulation ratio	10:1	10:1
Dimensions		
Height (mm)	780	780
Width (mm)	400	400
Depth (mm)	338	388
Weight		
Dry weight (kg)	36	38
Connections		
Flow & return	22mm	22mm
Gas	15mm	15mm
Safety valve	15mm	15mm
Condensate	21mm	21mm
Electrical data		
Voltage (V/Hz)	230/50	230/50
Flue details (concentric)		
Maximum horizontal flue length including rear flue (60/100mm)	7.8m	7.85m
Maximum vertical flue length (60/100mm)	8.8m	8.85m
Maximum horizontal flue length (80/125mm)	20m	14.85m
Maximum vertical flue length (80/125mm)	21m	15.85m
Flue details (twin pipes)		
Maximum horizontal flue length (80/80mm)	50/50m	38/38m
Maximum vertical flue length (80/80mm)	50/50m	38/38m
Efficiency		
ErP seasonal space heating energy efficiency (class/%)	A/93	A/93
SAP 2009 efficiency (%)	89.5	89.1
NOx class	5	5

ENERGY SAVING CONTROLS AND OPTIONS

Description	Code
OpenTherm RF programmable room thermostat ⁽³⁾	20050690
Weather compensation sensor ⁽²⁾	2359259
Relay ⁽³⁾ for use with weather compensation sensor	29450144
Spacing frame	2359689
Mynute i LPG conversion kit	20069593
Pipe cover	518
Condense pump	404
Magnetic filter	29450199

⁽¹⁾ Subject to registration and annual service. ⁽²⁾ Autostop activation device required. ⁽³⁾ Contact Vokèra Technical Helpline for advice



Fully compliant with the Energy-related Products Directive. Further savings can be achieved when installed with a weather compensation sensor or OpenTherm control.

5 year parts and labour warranty.⁽¹⁾

Exceptional modulation ratio of 10:1 maximises efficiency and comfort for end-user.

Simple to use back-lit LCD display ensures end-users can easily operate and adjust the appliance.

Rear flue option as well as the standard top flue option provides a versatile installation. Other flueing options available are; horizontal, vertical and twin flue.

Front mounted heat exchanger assists in simple maintenance. Our in-house patented heat exchanger incorporates a unique radial design utilising an extruded aluminium alloy. Aluminium has excellent thermal transfer properties and our updated design incorporates a new profile that inhibits the build-up of condensate residues, thereby significantly reducing the frequency of cleaning.

Built-in relay enables use of a wide variety of external controls and switching devices.

Dual temperature range - easily configured to suit under-floor heating systems, with two built-in temperature ranges to suit either high or low temperature systems.

Low pressure loss reduces noise and increases pump performance.

Designed for easy installation with standard Vokèra pipework layout enabling trouble free replacement of older Vokèra models.

Simple commissioning; only minimal adjustments are required after installation and automatic modulation eliminates the need to range rate the boiler.

Low NOx - Class 5 performance.

Anti-seize function protects the pump from sticking during long periods of inactivity.

Anti-cycling control prevents energy wasteful on/off cycling and reduces wear and tear.

Built-in frost protection, which protects the appliance from damage during periods of cold weather.

Standard Autostop disabling function⁽²⁾ that automatically changes the current operating mode and moves it permanently into the standby mode, helping Registered Social Landlords fulfill their obligation of an annual gas safety check. Autostop will only operate after a pre-defined period of time has elapsed and if it has been activated during commissioning.

Registered Address: Vokèra Ltd Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG

Email: enquiries@vokera.co.uk Web: www.vokera.co.uk Tel: 0844 391 0999 Fax: 0844 391 0998

Vokèra Ireland West Court, Callan, Co Kilkenny, R95 PW40 Tel: 056 775 5057 Fax: 056 775 5060

Vokèra Limited reserve the right to change specification without prior notice. Consumers statutory rights are not affected. E&OE
Company Reg No: 1047779



Search Vokera Ltd